

**SPECIFICATION**  
**(Sprint Docket No. 1705)**

**TO ALL WHOM IT MAY CONCERN:**

5           Be it known that we, **Manish MANGAL**, a citizen of India and a resident of Overland  
Park, Kansas, and **Kevin R. O'CONNOR**, a citizen of the United States and a resident of  
Olathe, Kansas, have invented a new and useful:

**METHOD AND SYSTEM FOR MULTICASTING  
MESSAGES TO SELECT MOBILE RECIPIENTS**

10           the following of which is a specification.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195

## **BACKGROUND**

### **1. Field of the Invention**

The present invention relates to telecommunications and, more particularly, to a method and system for broadcasting or multicasting a message to a specific group of mobile stations in a cellular wireless communications system.

### **2. Description of Related Art**

The advent of wireless telecommunications, such as cellular telephony, has extended the functionality available to wireless users: Just as a user can operate a cellular telephone or other mobile station (MS) to place a voice call to virtually any telephone number, a user can also operate a suitably equipped MS (such as, for example, a web-enabled wireless telephone) to place a data call to virtually any remote computer. Once such a connection is established, a remote computer can send data to the MS, much as a remote computer might send data to any personal computer connected to the Internet.

In a typical cellular radio communications system (i.e., a wireless telecommunications network), an area is divided geographically into a number of cell sectors, each defined by a radio frequency (RF) radiation pattern or air interface from a respective base transceiver station (BTS) antenna. A number of MSs (such as cellular telephones, personal digital assistants (PDAs) and/or other devices) may operate concurrently in a given cell sector, all communicating via the air interface with a common BTS. In turn, the BTSs from a number of cell sectors may communicate concurrently with a common base station controller (BSC), which may function to aggregate and control traffic for the multiple BTSs. A number of BSCs may then communicate concurrently with a common gateway, such as a packet data serving node (PDSN) or mobile switching center (MSC), which may function to set up and connect communications to or from other entities.

The BTS, BSC and gateway, in combination, comprise a radio network that provides network connectivity for an MS.

Generally, a user's MS is allocated a dedicated channel over which data may be sent and received. However, there are a number of specialized services that multiple wireless customers may find desirable. Examples of services that may be sent to multiple users could include:

- Location-based advertising;
- Vertical services, maintenance, and administrative messages
- Public information services, such as sports scores, traffic conditions, weather alerts, etc.;
- Video clips of newsworthy events; and
- Audio and video streaming.

In some specialized services, a number of MSs in a cell sector (or even all customers in the cell sector) would receive the same message. This does not present much of a problem when only a few users are to receive the data, but can tax a network's capacity as more users receive the same message. One resource that can be taxed is the air interface. The air interface between MSs and the radio network is a scarce resource, and its use should be conserved whenever possible. In addition, as high-bandwidth applications become more commonplace, the capacity between other entities and links in wireless communications networks may also be taxed. As an example, if a BTS is to support a number of concurrent high-bandwidth communications with multiple MSs, the link between the BTS and the BSC must support all of that traffic at once.

The link between a BTS and BSC, though, is typically a transmission line with a finite bandwidth. Similarly, the link between the BSC and a gateway such as a PDSN or MSC is typically a transmission line with finite bandwidth. Of course, it is possible to increase traffic capacity between various network elements by simply adding more transmission lines. Adding transmission lines, though, can be very expensive, since it requires a provider to either physically add the lines, or to lease additional lines from a local exchange carrier (LEC). Leasing lines from LECs to increase the traffic capacity between network elements can, in fact, be a significant portion of a cellular provider's total operating cost.

Thus, when a particular message (especially, but not necessarily, one requiring a significant amount of available bandwidth) is to be sent to a relatively large number of MSs within a cell sector (or to multiple cell sectors), a system for transmitting the message that conserves the cellular system's bandwidth is a significant improvement over a multicast system that transmits messages to cell sectors indiscriminately. Moreover, it would also be desirable to control which users have access to specialized services so that users who want such services can be required to pay for them, and also so that users who do not want the services are not bothered by unwanted messages.

## SUMMARY

The present invention is directed to an improved mechanism for transmitting data to multiple MSs in a cellular wireless communication network. The invention generally does this by (i) maintaining in a network entity a record of which MSs are in a given multicast group, (ii) maintaining in a network entity a record of which sectors are currently serving one or more members of the multicast group (which can be referred to as "sectors of interest"), (iii) providing each such MS with a key to facilitate receipt of a multicast or broadcast message, and (iv) multicasting or broadcasting the message to only the sectors of interest. Various network arrangements and processes can be employed to carry out these functions.

In an exemplary embodiment, each message that is to be sent can be an IP message, sent over a PPP channel to a 3G MS. The PPP channel could be established between a PDSN and the 3G MS. In this regard, the basic network architecture can include multiple BTSs coupled to a BSC. The BSC may then be coupled to the PDSN, which in turn is coupled to a packet-switched network such as the Internet. (The BSC may also be conventionally coupled to an MSC, which provides circuit-switched connectivity with the public-switched telephone network (PSTN) as well).

In the exemplary embodiment, to achieve the functions described above, the basic architecture of a cellular communications network can be modified to include the following:

(a) a Radio Network Multicast Server (RNMS) communicatively coupled with, or integrated into, the BSC, (b) a Multicast Session Manager (MSM) communicatively coupled with the PDSN, (c) a Multicast Application Server (MAS) communicatively coupled with the PDSN; and (d) an MS client, for filtering (for example, at the radio link layer) incoming messages

on a broadcast channel, so that higher levels of the protocol stack receive a given broadcast message only if the filter allows it. In the exemplary embodiment, valuable network resources can be conserved by transmitting multicast or broadcast messages only to BTSs that serve cell sectors with MSs of the multicast groups present in those cell sectors. For example, if MSs authorized to receive a particular multicast service are present in a first cell sector, but no such MSs are present in a second cell sector, the message will only be sent to the first cell sector. Thus, all of the entities and communication links between at least the BSC and the BTS of the second cell sector will not experience any increase in traffic due to the messages sent to MSs in the first cell sector.

These as well as other aspects and advantages of the present invention will become apparent to those of ordinary skill in the art by reading the following detailed description, with appropriate reference to the accompanying drawings.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

An exemplary embodiment of the present invention is described herein with reference to the drawings, in which:

5           Figure 1 is a simplified block diagram of a communication system for carrying communications between a mobile station and remote network entities in which the exemplary embodiment can be implemented;

          Figure 2 is a block diagram of a radio network multicast server for use in accordance with the exemplary embodiment;

10          Figure 3 is a simplified block diagram of a mobile station suitable for use with the exemplary embodiment;

          Figure 4 is a flow chart depicting functions performed in accordance with the exemplary embodiment;

15          Figure 5 is a block diagram of database table that may be used in the exemplary embodiment; and

          Figures 6 through 8 are flow charts depicting functions performed in accordance with the exemplary embodiment.

**DETAILED DESCRIPTION OF**  
**AN EXEMPLARY EMBODIMENT**

Referring to the drawings, Fig. 1 is a generalized block diagram of a communication network 10 suitable for communications between one or more MSs and various network entities. As shown in Fig. 1, the network 10 may include a radio network that comprises various network entities, such as: base transceiver stations (BTSs) 20, 22, and 24; radio network multicast router/server (RNMS) 26; base station controller (BSC) 28; and packet data serving node (PDSN) 30, such as a CommWorks<sup>®</sup> Total Control<sup>®</sup> 2000 or the like. In addition, BSC 28 may be coupled to a mobile switching center (MSC) such as MSC 40, as in conventional cellular networks. Because BTSs 20, 22, 24, BSC 28, PDSN 30, and MSC 40 can be conventional components of a radio network, they are not described in detail here.

PDSN 30 serves as an interface between the radio network and a packet-switched network such as packet-switched network 36 (which may be the Internet). In the exemplary embodiment, a multicast application server (MAS) such as MAS 38, an authentication, authorization, accounting (AAA) server such as AAA server 34, and a multicast session manager such as MSM 32 may be communicatively coupled to packet-switched network 36 (and thus ultimately to the radio network via PDSN 30). It should be noted that MSM 32, AAA server 34, and MAS 38 are functional entities, and any or all of the functions performed by these entities could be integrated into a single entity (or other, multiple entities that perform one or more of the functions in combination). Furthermore, any or all of MSM 32, AAA server 34, and MAS 38 could be directly coupled rather than via packet-switched network 36.



For clarity only, multiple network entities, such as RNMSs, PDSNs, BSCs, MSMs, and MASs have been omitted from the drawings, although a network in which the invention may be implemented could include more than one RNMS, PDSN, BSC, MSM, and MAS.

MAS 38 may generally store and periodically transmit a range of multicast content for reception by MSs that belong to a multicast group, each multicast being associated with a particular IP multicast address. MAS 38 may be a server on the IP core network (i.e., the Internet). In the exemplary embodiment, MAS 38 may not be co-located with a particular RNMS, although it could be. Instead, MAS 38 would be regionally placed and could thus be more readily accessed by multiple RNMSs via conventional network routers (not shown) within packet-switched network 36.

MSM 32 can provide, upon request from MSs, keys, filters, or masks needed by MSs to enable them to receive multicasts. MSM 32 may be in communication with AAA server 34 and can thus verify that any mobile station requesting to join a multicast group is authorized to join the group by communicating with AAA server 34

RNMS 26 may access a record or records that correlate radio network cell sectors of interest with particular multicast addresses. RNMS 26 signals the packet-switched network to receive multicast data packets sent from MAS 38 that have multicast addresses that correspond to sectors of interest, as indicated by the record or records. Upon receipt of such multicast packets, RNMS 26 may forward copies of the multicast packets to sectors of interest.

AAA server 34 may be a conventional component as described for a third-generation wireless system in ITU IMT-2000 requirements document Q.1701. AAA server 34 generally maintains account and authorization information as well as user profiles for MSs

served by the radio network. For example, AAA server 34 could maintain a record of which, if any, multicasts an MS is authorized to receive, as well as for how long. Thus, if a user wished to terminate a multicast service at the end of a given billing period, AAA server 34 could update its record at the end of the period and the MS's request for multicasts beyond the billing period would not be authorized.

MSs 12, 14, 16, and 18 may access the packet-switched network 36 or another network, such as the PSTN (not shown), via the radio network. In operation, an MS may send, via a BTS or BSC, a "join" message to RNMS 26, indicating a request to join a particular multicast group. The join message may be an IP message transmitted via a common channel in the radio network. When a BTS or BSC receives such a join message, the BTS or BSC may programmatically add to the IP message an indication of the MS's current cell sector; the join message may then be forwarded to RNMS 26. As MSs join a given multicast group, RNMS 26 could thus get an indication of which cell sectors currently serve those MSs. RNMS 26 can maintain this information in the form of a database table that lists, for each multicast group, the cell sectors currently serving MSs that are in the multicast group. RNMS 26 could be updated in real time (described in detail below) as multicast group MSs move through the network, ensuring efficient use of the radio network.

The connections of all the entities shown in Fig. 1 are logical rather than physical; as just one example, RNMS 26 could be physically connected between BSC 28 and PDSN 30 without affecting the functionality of the present invention.

Within network 10, multiple communications devices, such as MSs 12, 14, 16, (wireless telephones) and 18 (a web-enabled PDA), may be communicatively coupled with BTS 20, 22, and 24 as shown. Although MSs 12, 14, and 16 are illustrated as wireless

telephones, they may take any suitable form, such as (without limitation) wireless modems, wireless PDAs (like MS 18), or two-way pagers. MSs 12-18 may communicate with BTS 20-24 using an air interface as set forth in TIA/EIA/IS-2000. Further, MSs 12-18 could be part of a cellular system that uses another technology, such as AMPS, TDMA, DECT, GSM, PCS, or PWT; the cellular technology used is not necessarily critical to all embodiments of the present invention. Although MSs 12-18 are capable of normal voice communications via BSC 28 and MSC 40, this description will focus primarily on data communications using the network entities of network 10.

In the exemplary embodiment, MSs could join multicast groups as follows. A user with an MS, such as MS 12, might initiate a request to receive a multicast by, for example, turning on the MS or selecting a menu item on the MS's display. The request may include an option service code or other indicator that indicates packet-data. The request could first be forwarded from BSC 28 to MSC 40. MSC 40 may detect the option service code (or otherwise detect a data call) and responsively signal BSC 28 to send the message to PDSN 30 (rather than to MSC 40 as in a voice call). A PPP session could then be established between MS 12 and PDSN 30.

Next, a client (i.e., a set of software instructions) on MS 12 could set up a data communication session with MSM 32 via BTS 20, BSC 28, PDSN 30 and packet-switched network 36. MSM 32 could then authorize the user for access to private (or other) group multicasts, and transmit (using TCP/IP or a standard internet key exchange protocol, for example) a key or filtering mask to MS 12 during the data communication session to enable MS 12 to receive multicast or broadcast packets. MSM 32 could implement the authorization process by communicating with a registrar, such as AAA server 34, which

may maintain records of which users are authorized to receive multicasts, among other records (e.g., subscriber profiles). MS registration could also occur with other types of registrars, such as a home location register or a service agent (not shown). As an alternative to "on-the-fly" MS registration, an MS could be pre-provisioned by a service provider--that is, the MS could have a key or mask installed at a facility rather than over a communication channel.

Multicast messages may originate as follows. Periodically, or based on triggers from other network entities or MSs, MAS 38 may transmit multicast content to a conventional router (not shown) within packet-switched network 36. As an illustration, assume that only MS 12 and MS 18 are authorized to receive private group multicasts with a particular multicast address. RNMS 26 could receive the multicast content transmitted from MAS 38 via packet-switched network 36. When RNMS 26 receives an IP multicast packet from packet-switched network 36, it may send duplicates of the packet to each cell sector that is bound to the particular IP multicast address, as indicated in a database table, in this case, the cell sectors serving MS 12 and MS 18. Thus, multicast packets may be sent from BSC 28 to BTS 20 and BTS 24 (and received by MS 12 and 18, within those sectors), but none are sent from BSC 28 to BTS 22, because BTS 22 is not serving any multicast group members.

A simplified block diagram of RNMS 26 is shown in Fig. 2. The exemplary embodiment of RNMS 26 shown in Fig. 2 may have a processor 44 (e.g., an integrated circuit microprocessor), a memory 46 (e.g., memory module, ROM, RAM, flash memory, hard disk), a radio network data link interface 48, and a packet-switched network interface 42, all of which may or may not be interconnected by a system bus. Memory 46 may include more than one physical element, such as built-in ROM, RAM, a hard disk, an optical

drive, a removable memory device, etc., and may also include as stored content: one or more multicast addresses, one or more cell sector identifiers; a set of stored logic by (e.g., computer instructions) executable by processor 44 to accept inputs via radio network data link interface 48 to update the information stored in memory 46 and to carry out various other functions described herein. The multicast addresses and cell sector identifiers may or may not be stored in the form of a database table, where each multicast address has one or more cell sector identifiers associated with it in the table. Provided with the present disclosure, those skilled in the art can readily prepare appropriate computer instructions to perform the functions described herein.

The radio network data link interface 48 may include input and output ports and individual links for each cell sector associated with RNMS 26. The individual links may be either logical or physical.

RNMS 26 may send multicast routing control packets to PDSN 30 and to packet-switched network 36 via packet-switched network interface 42. The multicast routing control packets may then be received by MAS 38, in order to establish multicast paths from MAS 38 to RNMS 26 via packet switched network 36 and PDSN 30. RNMS 26 may then receive (at packet-switched network interface 42) IP multicast packets transmitted from MAS 38. The packet-switched network interface 42 may also be connected directly to the packet-switched network, bypassing PDSN 30.

The particular configuration shown in Fig. 2 is not necessarily critical to the functioning of all embodiments of the present invention. For example, a device without a system bus that has a memory and processor contained in one integrated circuit could be used instead of a separate processor and memory.

Referring now to Figure 3, a functional block diagram of an exemplary MS, such as MS 12 or MS 18, is shown. As illustrated, the MS may include a processor 50, memory 52, a wireless communications interface 54, and a local communications interface 56, all of which may be coupled together via a system bus 58. Each of these functional components may take any of a variety of forms.

Memory 52, for instance, may include a set of machine language instructions executable by processor 50 to carry out various functions described herein. (Alternatively or additionally, the MS can embody various combinations of hardware, firmware and/or software to carry out the functions described). Further, memory 52 may include other elements, such as a multicast client that processes IP multicast or broadcast data and presents it to a user. Memory 52 may comprise one or more volatile or non-volatile elements, such as flash memory, optical memory, or magnetic storage.

Wireless communications interface 54 may establish communications with the radio network via an air interface. As such, wireless interface 54 may comprise software logic (e.g., CDMA encoding logic) and/or may comprise a transceiver suitable for interfacing between processor 50 and a radio frequency antenna (not shown).

For use in an alternative exemplary embodiment, local interface 56 may function as a port for sending and receiving communications with a service provider's computer (not shown). Local interface 56 may comprise a conventional pin-out port, an infrared port, an Ethernet (RJ-45) port, or any other suitable interface. Software keys, masks, or filters that enable the MS to receive and process multicast messages may be installed in the MS via local interface 56.

In the exemplary embodiment, the MS may be at least a 3G (or, more generally, a broadband) MS. A 3G MS has the capability of establishing, maintaining, and terminating packet data sessions with PDSNs. An MS that is less than a 3G MS could also be used in the exemplary embodiment, although data throughput may be lower.

5 Figure 3a illustrates a mobile IP protocol reference model that may be used with the exemplary MS to communicate with the PDSN 30. A similar protocol model could be used by the exemplary MS to communicate with the RNMS 26, except the PPP layer might not be used or may be replaced with a multicast data link layer protocol specific to the radio network used. As described, the exemplary MS may have a client or another component  
10 that enables it to establish, maintain, and terminate a PPP session with PDSN 30; the client may also enable the MS to receive (via the PDSN 30) and store a transmitted key or mask that allows the MS to receive and process multicast and/or broadcast data sent to it via RNMS 26. Specifically, a transmitted "key" could activate a process in the MS to cause it to recognize, at the MS's IP layer, datagrams with a particular multicast address. In such an  
15 implementation, the MS may have a fixed, relatively small number of multicast addresses that it may selectively listen for based on keys it may receive. Once activated to listen for certain multicast packets, multicast packets with the particular multicast address could be received by the client in the MS (i.e., the packets could be passed up the protocol stack to the client for further processing). In MSs that have not received a key, multicast packets  
20 could simply be discarded at the IP layer.

The application of a key or mask to pass authorized multicast data to the MS application may alternatively be performed at the data link protocol layer instead of at the IP protocol layer. In order for the radio network to transmit a multicast packet from the RNMS

26 to the MS, the radio network may require the use of a multicast group identifier at the data link layer. In that case, this multicast link layer identifier could be used instead of the multicast IP address in the filtering mechanism. Each IP multicast group address could have a corresponding link layer identifier, with each determinable from the other based on a simple translation algorithm.

As an alternative to pre-configured multicast addresses, a multicast address could be transmitted to, and stored in, the MS as a result of a registration and authorization from a network entity such as MSM 32 or AAA server 34. Once a multicast address is stored in the MS, the filtering of messages could proceed as described above. As yet another alternative to software filtering, multicast or broadcast packets could be filtered by a hardware device (such as a digital signal processor, or DSP) in the MS. As is known to skilled persons, such filtering can be performed at various different protocol layers; thus, filtering techniques other than those described here could also be implemented in the exemplary embodiment.

Figure 4 illustrates generally a set of functions that may be involved in an exemplary embodiment of the present invention. At step 60, MSs, such as MS 12 and MS 18 may request authorization to participate in a particular multicast group. A network entity, such as MSM 32, may receive the authorization request via PDSN 30 and packet-switched network 36. MSM 32 may verify, by communicating with AAA server 34, that MS 12 and 18 are authorized to receive the requested multicast messages, step 62. Once MS 12 and 18 are recognized by MSM 32, MSM 32 can send a filtering key or mask to MS 12 and MS 18, as shown at step 64 and described in detail above, to allow those MSs to further process multicast messages.



Then, at step 66, MS 12 and 18 may send "JOIN" messages to RNMS 26. As illustrated by step 68, MAS 38 may, based on either time or an event trigger (such as receipt of new data via packet-switched network 36), transmit multicast data to RNMS 26 via packet-switched network 36 and PDSN 30. At step 70, when RNMS 26 receives multicast data, it may route the data to only those cell sectors currently serving MSs that have requested (by sending "join" messages) to receive the multicasts. RNMS 26 is capable of making such routing decisions because it maintains (or has access to, via another network entity) a record that correlates particular multicast groups (by multicast address) to sectors of interest. A simplified example of such a record is shown in Table 1 of Fig. 5. Further, RNMS 26 may be a multicast-aware router/server, i.e., a router/server that can actively signal a packet network to receive multicast packets with destination addresses within the IP multicast range of 224.0.0.1 through 239.255.255.255.

In the exemplary embodiment, multicast data could be sent to BTS 20 and 24, which serve sectors of interest, but not to BTS 22, since MS 14, served by BTS 22, has not requested the multicast via a "join" message. Once BTS 20 and BTS 24 receive multicast packets, the packets may be forwarded to MS 12 and MS 18, respectively, and MS 12 and 18 may receive and further process the multicast packets (for example, by formatting and displaying, on MS 12 and 18, information contained in the packets in human-readable form), as shown at step 72.

Fig. 6 illustrates a set of functions that may be involved in enabling an MS to receive and process multicast messages. At step 80, an MS may send an origination (or registration) message, via air an interface, to BSC 28, which can then forward the message to an MSC 40. More specifically, to initiate registration in a multicast group, a user could, for example,

select a menu item on the MS, causing a registration message to be sent to MSC 40 via BSC 28. The origination/registration message may include information in a service option as defined by TIA/EIA-95, TIA/EIA-2000, or an equivalent standard, to determine that the call is a data call, rather than a voice call, as shown at step 82. MSC 40 can be configured to use this information and responsively send a message to BSC 28 to cause BSC 28 to transmit the data call to PDSN 30, as shown at step 84, rather than routing the call into the PSTN. Alternatively, MSC 40 could detect a data call using information other than that contained in a service option. For example, MSC 40 could recognize a data call based on the contents of OSI layer 4 (the transport layer). The method used to determine that a call is a data call is not necessarily critical to all embodiments of the present invention. PDSN 30 and the registering MS can then set up a PPP session, at step 86, and a client on the MS can set up a TCP/IP session with MSM 32, via PDSN 30 (step 88).

Next, as shown at step 90, MSM 32 can communicate with a registrar such as AAA server 34 (either via packet-switched network 36, another suitable data link, or direct connection) to determine that the MS is authorized to join the multicast group. AAA server 34 can maintain, separately or as part of a subscriber profile, a record of MSs that are authorized members of particular multicast groups. This information can be passed from the AAA server to MSM 32, making MSM 32 aware that a particular MS or group of MSs are authorized to receive multicast messages. Alternatively, the registrar function of AAA server 34 could be incorporated into MSM 32. Once MSM 32 recognizes an MS as an authorized group member, MSM 32 can transmit to the MS a filtering key/mask to the MS to enable it to receive and process multicast messages, as shown at step 92. If a multicast message reaches an MS in a sector of interest and the MS does not have a filtering

key/mask, the MS will be unable to further process the message. In other words, the message will not effectively be received at an unauthorized MS.

The architecture of the present invention also supports data broadcasting as well as cell-specific multicasting. For example, RNMS 26 can interpret a broadcast-specific IP address as an address whose data is to be forwarded to all cell sectors. For filtering at the MS at the data link layer, a common link-layer broadcast identifier that would pass through all MS filters can be used by RNMS 26 when it forwards broadcast packets, enabling all MSs to further process the broadcast data. As another example, multicasts may be designated for all MSs at particular cell sectors--e.g., for public announcements on traffic conditions. For cell-specific multicasts, RNMS 26 may recognize that packets with certain IP multicast addresses are to be forwarded to specific cell sectors only. In that case, sectors 20 and 24 in Table 1 would be sectors of interest not due to the presence of MSs that are multicast group members, but because the multicast address 224.1.2.3 is "linked" to those sectors. Thus, multicast information that is only pertinent to a particular geographic area will not follow users as they move out of the area.

To facilitate the routing of multicast messages, RNMS 26 may use IETF Protocol-Independent Multicast to advertise to IP core routers the presence of multicast group members on the radio network.

Some steps that may be involved in the process of an MS joining a multicast group are illustrated in Fig. 7. First, an MS may send a "Join" message to RNMS 26 to indicate that it is ready and authorized to receive multicast messages (step 100). More specifically, the MS may send an IP-encapsulated IETF Internet Group Membership Protocol format message in radio network link layer framing to a BTS or BSC 28 over an access channel (or

other common channel) in the radio network. When a BTS or BSC 28 receives the join message, either the BTS or BSC 28 may modify or encapsulate the message (e.g., add additional data in the link layer framing of the packet data being sent) with an indicator or identifier defining the MS's current cell sector. The message can then be forwarded to RNMS 26, as shown at step 102. Next, RNMS 26 can update its database table to include the MS's current sector as a sector of interest so that multicasts intended for the MS will be routed to that sector, as shown at step 104. The database table update could also include adding or deleting multicast addresses as necessary to maintain accuracy.

Figure 8 illustrates some functions that may be used to ensure that the multicast database is current even after MSs leave and enter sectors of interest. As shown at step 110, a network entity such as RNMS 26 (or another entity, via the BTS), can periodically multicast queries, such as internet group management protocol (IGMP) queries, to a cell sector or sectors to determine if there is still at least one MS in a sector that is a multicast group member. If there is no such MS in the sector, the RNMS will be "aware" that the sector is no longer a sector of interest, as shown at step 112. If the sector is no longer a sector of interest, RNMS 26 could update its database table to remove the cell sector and stop routing multicast messages to the associated BTS, as shown at step 114. Conversely, if there is at least one MS in a queried sector that is a multicast group member, RNMS 26 could update its database table to add the sector as a sector of interest if the sector was not a sector of interest prior to the query, as shown at step 116.

Thus, RNMS 26 could maintain the accuracy of a database table in substantially real-time as MSs move through the network.

An exemplary embodiment of the present invention has been described above.

Those skilled in the art will understand, however, that changes and modifications may be made to this embodiment without departing from the true scope and spirit of the present invention, which is defined by the claims.

McDONNELL BOEHLEN  
HULBERT & BERGHOF  
300 SOUTH WACKER DRIVE  
CHICAGO, ILLINOIS 60606  
TELEPHONE (312) 913-0001